

ENERFUEL WITH LUBRICITY™



The Hi-Tech Treatment and Lubricity Improver for today's Low and Ultra-Low Sulfur Diesel Fuels

EnerFuel with Lubricity™ is the All-Season Treatment to Add Lubricity to Low and Ultra-Low Sulfur Fuels. It will Improve Fuel Efficiency, Increase Power, Reduce Emissions, Reduce Engine Wear, Stabilize Fuel, and Eliminate the Harmful Effects of Water in the Fuel.

EnerFuel with Lubricity™ is an organic based product that is a powerful fuel system cleaner. It dissolves the gum, varnish, and carbon deposits that distort fuel injector spray patterns and damage delicate injector and pump components. Cleaning these parts allows your engine to operate with all the power and efficiency that the manufacturer designed into it. To this we add a Hi-Tech Lubricant that restores the Lubricating to Fuels to reduce wear and extend engine life.

EnerFuel with Lubricity™ causes fuel to be atomized better by the fuel injectors for more efficient combustion and reduced emissions.

EnerFuel with Lubricity™ slows the oxidation of fuel, stabilizing it.

EnerFuel with Lubricity™ contains no harmful alcohols that can damage gaskets and seals.

EnerFuel with Lubricity™ chemically removes the water found in all diesel fuel. Water that can corrode metal parts, water that mixes with the sulfur in fuel to create damaging sulfuric acid, water that can freeze in filters and fuel lines, water that supports the growth of spores and bacteria into a thick sticky slime that clogs fuel injectors and plugs fuel filters. By eliminating water, you can prevent all of these problems.

EnerFuel with Lubricity™ will help hold wax in suspension, slowing the growth of crystals that plug filters in cold weather.

With today's Hi-Tech electronically controlled engines, the need to make older equipment last longer, and the difficulty in obtaining fuels that meet the manufacturers requirements, the need for a high quality fuel treatment is more important than ever before.

EnerFuel with Lubricity™ is a highly concentrated formula uses only 32 ounces to treat 250 gallons.

ENERFUEL WITH LUBRICITY™

- Adds Lubricity to Fuels
- Clean Fuel Injectors and Pumps
- Reduces Oxidation to Stabilize Fuel
- Eliminates Water
- Organic Based Formula with No Harmful Alcohols
- Improves Fuel Atomization for More Power, Greater Efficiency, and Reduced Emissions

Directions:

For best results, use every time you fuel, adding contents to fuel tanks prior to fueling. The fueling process will ensure that complete and proper mixing takes place.

Use 32 ounces for each 250 gallons of fuel (1:1000 treatment ratio).

First time users can use 32 ounces for each 125 gallons to speed the cleaning process.

When operating in extreme conditions (marine, high humidity, very cold weather) it is acceptable to use the 32 ounces per 125 gallons dosage on a regular basis.

In Cold Weather we suggest the use of Polar Flow or Complete Fuel Treatment to prevent fuel from gelling and to improve cold weather operation.

For more information please consult the Material Safety Data Sheet for this product.

All used and unused product and its containers should be disposed of in accordance with all local, state, and federal regulations.

Keep This Product Out Of Reach of Children

Notice to Purchaser: Enertech Labs, Inc. provides no warranty of any kind with respect to the product whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

Packaging:

Package Size	Treats	Quantity/Case	Part Number	UPC
32 oz. Bottle	250 US Gallons	12 per case	10405	877016004052
1 US Gallon	1,000 US Gallons	4 per case	10406	877016004069
5 US Gallon	5,000 US Gallons	1	10407	877016004076
55 US Gallons	55,000 US Gallons	1	10409	877016004090
275 US Gallons	275,000 US Gallons	1	10400	877016004007

Enertech Labs, Inc.
Peak Performance Specialists
Buffalo, NY (800) 759-2080
www.enertechlabs.com